

Berker Integro Module inserts

Tiny – but virtually indispensable. The round function elements of the module inserts give every unit its unmistakable character. With their minimal dimensions and shallow installation depths, they are extremely versatile. The incredible depth of the product range means you have an excellent variety of functions available, and thus the optimal solution in each case.



SCHUKO socket outlets	22
SCHUKO socket outlets with "SNAP IN"	29
Socket outlets with earthing contact	38
Socket outlets with earthing pin	41
Socket outlets without earthing contact	44
Connecting devices 12 V	45
USB charging sockets	47
TV/multimedia	48
Rocker switch	54
Rocker push-button	58
Blind push-button	60
Reverse polarity push-button	60
Appliance switch	62
1 - 10 V control units	62
Accessories	63



Marked items are suitable for splash-protected IP44 installation when used in conjunction with the corresponding sealing set.

SCHUKO socket outlets

- for 4-hole screw fitting

SCHUKO socket outlets with plug-in terminals

- thermoplastic centre plates and bases
- contacts made of copper alloy

 Marked items are only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing (order no. 9 1853), frame with hinged cover and imprint "IP44" and contact protection box.



SCHUKO socket outlet

- plug-in terminals



Rated voltage 250 V~

Rated current 16 A

Earth bracket clamping forces according to TNO requirements.

Standard NEN 1010

Connection terminals according to IEC 60884-1

Design	Order no.	PU
brown matt	8 4778 25 01	200
anthracite matt	8 4778 25 05	200
grey matt	8 4778 25 06	200
polar white matt	8 4778 25 02	200
brown matt	9 4778 25 01	10
anthracite matt	9 4778 25 05	10
grey matt	9 4778 25 06	10
polar white matt	9 4778 25 02	10
black matt	9 4778 25 03	10



SCHUKO socket outlet

- enhanced contact protection
- plug-in terminals



Rated voltage 250 V~

Rated current 16 A

Earth bracket clamping forces according to TNO requirements.

Standard NEN 1010

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

Design	Order no.	PU
brown matt	8 4779 25 01	200
anthracite matt	8 4779 25 05	200
grey matt	8 4779 25 06	200
polar white matt	8 4779 25 02	200
brown matt	9 4779 25 01	10
anthracite matt	9 4779 25 05	10
grey matt	9 4779 25 06	10
polar white matt	9 4779 25 02	10
black matt	9 4779 25 03	10



SCHUKO socket outlets with screw terminals

- thermoplastic centre plates
- duroplast base
- contacts made of copper alloy



Marked items are only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing (order no. 9 1853), frame with hinged cover and imprint "IP44" and contact protection box.



SCHUKO socket outlet

▶ 210

- screw terminals



Rated voltage

250 V~

Rated current

16 A

Connection terminals according to IEC 60884-1

Suitable for

Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 1820 ..
9 188 ..
9 191 ..
9 1933
Optional
Sealing for IP44 applications
Frame with hinged cover and imprint "IP44"

Page

63
63
63
64
78
77

Design

Order no.

PU

brown matt

8 4185 25 01

200

anthracite matt

8 4185 25 05

200

grey matt

8 4185 25 06

200

polar white matt

8 4185 25 02

200

black matt

8 4185 05

200

brown matt

9 4185 25 01

10

anthracite matt

9 4185 25 05

10

grey matt

9 4185 25 06

10

polar white matt

9 4185 25 02

10

black matt

9 4185 05

10



SCHUKO socket outlet

▶ 210

- enhanced contact protection
- screw terminals



Rated voltage

250 V~

Rated current

16 A

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

Suitable for

Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 1820 ..
9 188 ..
9 191 ..
9 1933
Optional
Sealing for IP44 applications
Frame with hinged cover and imprint "IP44"

Page

63
63
63
64
78
77

Design

Order no.

PU

brown matt

8 4195 25 01

200

anthracite matt

8 4195 25 05

200

grey matt

8 4195 25 06

200

polar white matt

8 4195 25 02

200

black matt

8 4195 05

200

brown matt

9 4195 25 01

10

anthracite matt

9 4195 25 05

10

grey matt

9 4195 25 06

10

polar white matt

9 4195 25 02

10

black matt

9 4195 05

10



SCHUKO socket outlet 45°			210
	- screw terminals	- for diagonal installation	
			
	Rated voltage	250 V~	
	Rated current	16 A	
	Connection terminals according to IEC 60884-1		
Design	Order no.		PU
brown matt	8 4185 25 21		200
anthracite matt	8 4185 25 25		200
grey matt	8 4185 25 26		200
polar white matt	8 4185 25 22		200
black matt	8 4185 25		200
black matt	9 4185 25		10

SCHUKO socket outlets with insulation-piercing terminals

- New: Insulation-piercing terminals (IPT) for quick and easy connection with the joining tool, order no. 8 1726 25 81
- VDE approval
- Up to 2 flexible conductors with a cross section of 2.5 mm² can be connected for each IPT contact; wires do not have to be stripped in advance.
- Enables multiple socket outlets to be looped through without breaking the conductors.
- IPT contacts made from copper alloy, tin-plated
- thermoplastic centre plates and bases
- Base with snap-on safety cap

Marked items are only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing (order no. 9 1853 01) and frame with hinged cover and imprint "IP44".

SCHUKO socket outlet			212
	- insulation-piercing terminals		
			
	Rated voltage	250 V~	
	Rated current	16 A	
	Conductor cross-section (flexible)	2.5 mm ²	
Earth bracket clamping forces according to TNO requirements.			
Not suitable for contact protection boxes (cavity walls).			
Connection terminals according to IEC 60884-1			
Design	Order no.		PU
anthracite matt	★ 8 4800 25 05		200
grey matt	★ 8 4800 25 06		200
polar white matt	★ 8 4800 25 02		200
black matt	★ 8 4800 25 08		200
red matt	★ 8 4800 25 07		200
green matt	★ 8 4800 25 03		200
orange matt	★ 8 4800 25 04		200



SCHUKO socket outlet

- enhanced contact protection
- insulation-piercing terminals



Rated voltage	250 V~
Rated current	16 A
Conductor cross-section (flexible)	2.5 mm ²

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

Suitable for Optional

Sealing IP44 for socket outlets with insulation displacement contacts	9 1853 01
Frame with hinged cover and imprint "IP44"	8 1828 ..

Order no.

Page

212

79

77

Design	Order no.	PU
anthracite matt	★ 8 4801 25 05	200
grey matt	★ 8 4801 25 06	200
polar white matt	★ 8 4801 25 02	200
black matt	★ 8 4801 25 08	200
red matt	★ 8 4801 25 07	200
green matt	★ 8 4801 25 03	200
orange matt	★ 8 4801 25 04	200



SCHUKO socket outlet with control LED

- insulation-piercing terminals



Rated voltage	250 V~
Rated current	16 A
LED current	1 mA
Conductor cross-section (flexible)	2.5 mm ²

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

- with green control LED as function light

Suitable for Optional

Frame with hinged cover and imprint "IP44"	
Sealing IP44 for socket outlets with insulation displacement contacts	9 1853 01

Order no.

Page

upon request

79

Design	Order no.	PU
anthracite matt	★ 8 4800 25 15	200
grey matt	★ 8 4800 25 16	200
polar white matt	★ 8 4800 25 12	200
black matt	★ 8 4800 25 18	200
red matt	★ 8 4800 25 17	200
green matt	★ 8 4800 25 13	200
orange matt	★ 8 4800 25 14	200



New



SCHUKO socket outlet with control LED

▶ 212



- enhanced contact protection
- insulation-piercing terminals



Rated voltage	250 V~
Rated current	16 A
LED current	1 mA
Conductor cross-section (flexible)	2.5 mm ²

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

- with green control LED as function light

Suitable for
Optional

Order no.

Page

Frame with hinged cover and imprint "IP44"		upon request
Sealing IP44 for socket outlets with insulation displacement contacts	9 1853 01	79

Design	Order no.	PU
anthracite matt	★ 8 4801 25 15	200
grey matt	★ 8 4801 25 16	200
polar white matt	★ 8 4801 25 12	200
black matt	★ 8 4801 25 18	200
red matt	★ 8 4801 25 17	200
green matt	★ 8 4801 25 13	200
orange matt	★ 8 4801 25 14	200



New



SCHUKO socket outlet 45°

▶ 212



- insulation-piercing terminals



Rated voltage	250 V~
Rated current	16 A
Conductor cross-section (flexible)	2.5 mm ²

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

- for diagonal installation

Suitable for
Optional

Order no.

Page

Sealing IP44 for socket outlets with insulation displacement contacts	9 1853 01	79
Frame with hinged cover and imprint "IP44"	8 1828 ..	77

Design	Order no.	PU
anthracite matt	★ 8 4850 25 05	200
grey matt	★ 8 4850 25 06	200
polar white matt	★ 8 4850 25 02	200
black matt	★ 8 4850 25 08	200
red matt	★ 8 4850 25 07	200
green matt	★ 8 4850 25 03	200
orange matt	★ 8 4850 25 04	200





SCHUKO socket outlet 45°

- enhanced contact protection
- insulation-piercing terminals



Rated voltage	250 V~
Rated current	16 A
Conductor cross-section (flexible)	2.5 mm²

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

- for diagonal installation

Suitable for	Order no.	Page
Optional		
Sealing IP44 for socket outlets with insulation displacement contacts	9 1853 01	79
Frame with hinged cover and imprint "IP44"	8 1828 ..	77

Design	Order no.	PU
anthracite matt	★ 8 4851 25 05	200
grey matt	★ 8 4851 25 06	200
polar white matt	★ 8 4851 25 02	200
black matt	★ 8 4851 25 08	200
red matt	★ 8 4851 25 07	200
green matt	★ 8 4851 25 03	200
orange matt	★ 8 4851 25 04	200



SCHUKO socket outlet 45° with control LED

- insulation-piercing terminals



Rated voltage	250 V~
Rated current	16 A
LED current	1 mA
Conductor cross-section (flexible)	2.5 mm²

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

- with green control LED as function light
- for diagonal installation

Suitable for	Order no.	Page
Optional		
Frame with hinged cover and imprint "IP44"		upon request
Sealing IP44 for socket outlets with insulation displacement contacts	9 1853 01	79

Design	Order no.	PU
anthracite matt	★ 8 4850 25 15	200
grey matt	★ 8 4850 25 16	200
polar white matt	★ 8 4850 25 12	200
black matt	★ 8 4850 25 18	200
red matt	★ 8 4850 25 17	200
green matt	★ 8 4850 25 13	200
orange matt	★ 8 4850 25 14	200



212




upon request
79

Design	Order no.	PU
anthracite matt	★ 8 4851 25 15	200
grey matt	★ 8 4851 25 16	200
polar white matt	★ 8 4851 25 12	200
black matt	★ 8 4851 25 18	200
red matt	★ 8 4851 25 17	200
green matt	★ 8 4851 25 13	200
orange matt	★ 8 4851 25 14	200



212



SCHUKO socket outlets with "SNAP IN"

- for catch fixing

SCHUKO socket outlets with "SNAP IN" and plug-in terminals


- thermoplastic centre plates and bases
- contacts made of copper alloy



Marked items are only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with corresponding frame with hinged cover and imprint "IP44".

Assembly instructions for IP44 socket outlets with SNAP IN and plug-in terminals

Not suitable for contact protection boxes!



Attention!

Only upon compliance with the assembly instructions the degree of protection IP44 is guaranteed.



SCHUKO socket outlet 45°, SNAP IN

- plug-in terminals



Rated voltage

250 V~

Rated current

16 A

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Standard NEN 1010

Connection terminals according to IEC 60884-1

Design

Order no.

PU

for installation wall thickness 1 mm (± 0.1 mm)

anthracite matt

8 4733 25 05

200

grey matt

8 4733 25 06

200

for installation wall thickness 1.8 mm (± 0.2 mm)

grey matt

8 4787 25 06

200

- with distance sealing ring
- for diagonal installation

**Suitable for
Optional**

Order no.

Page

Frame with hinged cover and imprint "IP44"

8 1828 ..

77

▶ 210



SCHUKO socket outlet 45°, SNAP IN			210
	- enhanced contact protection - plug-in terminals	- with distance sealing ring - for diagonal installation	
		Suitable for	Order no.
		Optional	Page
		Frame with hinged cover and imprint "IP44"	77
	Rated voltage	250 V~	
	Rated current	16 A	
	Earth bracket clamping forces according to TNO requirements.		
	Not suitable for contact protection boxes (cavity walls).		
	Standard NEN 1010		
	Connection terminals according to IEC 60884-1		
	Enhanced contact protection (child protection) according to IEC 60884-1		
	Design	Order no.	PU
	for installation wall thickness 1.8 mm (± 0.2 mm)		
	grey matt	8 4788 25 06	200
	for installation wall thickness 2.8 mm (± 0.2 mm)		
	grey matt	8 4731 25 06	200

SCHUKO socket outlet 45° with control LED, SNAP IN			210
	- enhanced contact protection - plug-in terminals	- with green control LED as function light - with distance sealing ring - for diagonal installation	
		Suitable for	Order no.
		Optional	Page
		Frame with hinged cover and imprint "IP44"	upon request
	Operating voltage	250 V~	
	Rated current	16 A	
	LED current	1 mA	
	Installation wall thickness	2 mm	
	Earth bracket clamping forces according to TNO requirements.		
	Not suitable for contact protection boxes (cavity walls).		
	Standard NEN 1010		
	Connection terminals according to IEC 60884-1		
	Enhanced contact protection (child protection) according to IEC 60884-1		
	Design	Order no.	PU
	for installation wall thickness 2 mm (± 0.2 mm)		
	anthracite matt	9 4713 25 05	200
	grey matt	9 4713 25 06	200
	polar white matt	9 4713 25 02	200
	red matt	9 4713 25 76	200
	green matt	9 4713 25 03	200
	orange matt	9 4713 25 04	200


SCHUKO socket outlets with "SNAP IN" and screw terminals

- thermoplastic centre plates
- duroplast base
- contacts made of copper alloy

 Marked items are only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with corresponding frame with hinged cover and imprint "IP44".

Assembly instructions for IP44 socket outlets with SNAP IN and screw terminals

Not suitable for contact protection boxes!



Attention!
Only upon compliance with the assembly instructions the degree of protection IP44 is guaranteed.

SCHUKO socket outlet 45°, SNAP IN



- screw terminals



Rated voltage
Rated current

250 V~
16 A

Not suitable for contact protection boxes (cavity walls).
Connection terminals according to IEC 60884-1

Design

for installation wall thickness 1 mm (± 0.1 mm)
grey matt

Order no.

8 4104 25 06

PU

200

▶ 210

SCHUKO socket outlet 45°, SNAP IN



- enhanced contact protection
- screw terminals



Rated voltage
Rated current

250 V~
16 A

Not suitable for contact protection boxes (cavity walls).
Connection terminals according to IEC 60884-1
Enhanced contact protection (child protection) according to IEC 60884-1

Design

for installation wall thickness 1.8 mm (± 0.2 mm)
grey matt

Order no.

8 4140 25 06

PU

200

▶ 210


SCHUKO socket outlets with "SNAP IN" and insulation-piercing terminals

- New: Insulation-piercing terminals (IPT) for quick and easy connection with the joining tool, order no. 8 1726 25 81
- VDE approval
- Up to 2 flexible conductors with a cross section of 2.5 mm² can be connected for each IPT contact; wires do not have to be stripped in advance.
- Enables multiple socket outlets to be looped through without breaking the conductors.
- IPT contacts made from copper alloy, tin-plated
- thermoplastic centre plates and bases
- Base with snap-on safety cap

 Marked items are only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with corresponding frame with hinged cover and imprint "IP44".

Assembly instructions for IP44 socket outlets with SNAP IN and insulation-piercing terminals

Not suitable for contact protection boxes!



Attention!
Only upon compliance with the assembly instructions the degree of protection IP44 is guaranteed.

New



SCHUKO socket outlet, SNAP IN

- insulation-piercing terminals



Rated voltage 250 V~
Rated current 16 A
Conductor cross-section (flexible) 2.5 mm²

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

- with distance sealing ring

Suitable for
Optional

Frame with hinged cover and imprint "IP44"

Order no.

8 1828 ..

Page

77

Design

Order no.

PU

for installation wall thickness 1 mm (± 0.1 mm)

anthracite matt	★ 8 4810 25 05	200
grey matt	★ 8 4810 25 06	200
polar white matt	★ 8 4810 25 02	200
black matt	★ 8 4810 25 08	200
red matt	★ 8 4810 25 07	200
green matt	★ 8 4810 25 03	200
orange matt	★ 8 4810 25 04	200

for installation wall thickness 2 mm (+0.1/-0.3 mm)

anthracite matt	★ 8 4820 25 05	200
grey matt	★ 8 4820 25 06	200
polar white matt	★ 8 4820 25 02	200
black matt	★ 8 4820 25 08	200
red matt	★ 8 4820 25 07	200
green matt	★ 8 4820 25 03	200
orange matt	★ 8 4820 25 04	200



Design	Order no.	PU
for installation wall thickness 3 mm (+0.1/-0.3 mm)		
anthracite matt	★ 8 4830 25 05	200
grey matt	★ 8 4830 25 06	200
polar white matt	★ 8 4830 25 02	200
black matt	★ 8 4830 25 08	200
red matt	★ 8 4830 25 07	200
green matt	★ 8 4830 25 03	200
orange matt	★ 8 4830 25 04	200



SCHUKO socket outlet, SNAP IN

- enhanced contact protection
- insulation-piercing terminals



Rated voltage	250 V~
Rated current	16 A
Conductor cross-section (flexible)	2.5 mm²

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

- with distance sealing ring

Suitable for Optional	Order no.	Page
Frame with hinged cover and imprint "IP44"	8 1828 ..	77

212



Design	Order no.	PU
for installation wall thickness 1 mm (± 0.1 mm)		
anthracite matt	★ 8 4811 25 05	200
grey matt	★ 8 4811 25 06	200
polar white matt	★ 8 4811 25 02	200
black matt	★ 8 4811 25 08	200
red matt	★ 8 4811 25 07	200
green matt	★ 8 4811 25 03	200
orange matt	★ 8 4811 25 04	200
for installation wall thickness 2 mm (+0.1/-0.3 mm)		
anthracite matt	★ 8 4821 25 05	200
grey matt	★ 8 4821 25 06	200
polar white matt	★ 8 4821 25 02	200
black matt	★ 8 4821 25 08	200
red matt	★ 8 4821 25 07	200
green matt	★ 8 4821 25 03	200
orange matt	★ 8 4821 25 04	200
for installation wall thickness 3 mm (+0.1/-0.3 mm)		
anthracite matt	★ 8 4831 25 05	200
grey matt	★ 8 4831 25 06	200
polar white matt	★ 8 4831 25 02	200
black matt	★ 8 4831 25 08	200
red matt	★ 8 4831 25 07	200
green matt	★ 8 4831 25 03	200
orange matt	★ 8 4831 25 04	200

New		SCHUKO socket outlet with control LED, SNAP IN	212
	- insulation-piercing terminals	- with green control LED as function light - with distance sealing ring	
		Suitable for Optional Frame with hinged cover and imprint "IP44"	Order no. upon request
	Rated voltage Rated current LED current Conductor cross-section (flexible)	250 V~ 16 A 1 mA 2.5 mm ²	Page upon request
	Earth bracket clamping forces according to TNO requirements. Not suitable for contact protection boxes (cavity walls). Connection terminals according to IEC 60884-1		
	Design	Order no.	PU
	for installation wall thickness 1 mm (± 0.1 mm)		
	anthracite matt	★ 8 4810 25 15	200
	polar white matt	★ 8 4810 25 12	200
	red matt	★ 8 4810 25 17	200
	green matt	★ 8 4810 25 13	200
	orange matt	★ 8 4810 25 14	200
	for installation wall thickness 2 mm (+0.1/-0.3 mm)		
	anthracite matt	★ 8 4820 25 15	200
	polar white matt	★ 8 4820 25 12	200
	red matt	★ 8 4820 25 17	200
	green matt	★ 8 4820 25 13	200
	orange matt	★ 8 4820 25 14	200
	for installation wall thickness 3 mm (+0.1/-0.3 mm)		
	anthracite matt	★ 8 4830 25 15	200
	polar white matt	★ 8 4830 25 12	200
	red matt	★ 8 4830 25 17	200
	green matt	★ 8 4830 25 13	200
	orange matt	★ 8 4830 25 14	200

New		SCHUKO socket outlet with control LED, SNAP IN	212
	- enhanced contact protection - insulation-piercing terminals	- with green control LED as function light - with distance sealing ring	
		Suitable for Optional Frame with hinged cover and imprint "IP44"	Order no. upon request
	Rated voltage Rated current LED current Conductor cross-section (flexible)	250 V~ 16 A 1 mA 2.5 mm ²	
	Earth bracket clamping forces according to TNO requirements. Not suitable for contact protection boxes (cavity walls). Connection terminals according to IEC 60884-1 Enhanced contact protection (child protection) according to IEC 60884-1		
	Design	Order no.	PU
	for installation wall thickness 1 mm (± 0.1 mm)		
	anthracite matt	★ 8 4811 25 15	200
	polar white matt	★ 8 4811 25 12	200
	red matt	★ 8 4811 25 17	200
	green matt	★ 8 4811 25 13	200
	orange matt	★ 8 4811 25 14	200
	for installation wall thickness 2 mm (+0.1/-0.3 mm)		
	anthracite matt	★ 8 4821 25 15	200
	polar white matt	★ 8 4821 25 12	200
	red matt	★ 8 4821 25 17	200
	green matt	★ 8 4821 25 13	200
	orange matt	★ 8 4821 25 14	200

Design	Order no.	PU
for installation wall thickness 3 mm (+0.1/-0.3 mm)		
anthracite matt	★ 8 4831 25 15	200
polar white matt	★ 8 4831 25 12	200
red matt	★ 8 4831 25 17	200
green matt	★ 8 4831 25 13	200
orange matt	★ 8 4831 25 14	200

New



SCHUKO socket outlet 45°, SNAP IN

▶ 212

- insulation-piercing terminals

- with distance sealing ring
- for diagonal installation



Rated voltage 250 V~
Rated current 16 A
Conductor cross-section (flexible) 2.5 mm²

Suitable for Optional	Order no.	Page
Frame with hinged cover and imprint "IP44"	8 1828 ..	77

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

Design	Order no.	PU
for installation wall thickness 1 mm (± 0.1 mm)		
anthracite matt	★ 8 4860 25 05	200
grey matt	★ 8 4860 25 06	200
polar white matt	★ 8 4860 25 02	200
black matt	★ 8 4860 25 08	200
red matt	★ 8 4860 25 07	200
green matt	★ 8 4860 25 03	200
orange matt	★ 8 4860 25 04	200
for installation wall thickness 2 mm (+0.1/-0.3 mm)		
anthracite matt	★ 8 4870 25 05	200
grey matt	★ 8 4870 25 06	200
polar white matt	★ 8 4870 25 02	200
black matt	★ 8 4870 25 08	200
red matt	★ 8 4870 25 07	200
green matt	★ 8 4870 25 03	200
orange matt	★ 8 4870 25 04	200
for installation wall thickness 3 mm (+0.1/-0.3 mm)		
anthracite matt	★ 8 4880 25 05	200
grey matt	★ 8 4880 25 06	200
polar white matt	★ 8 4880 25 02	200
black matt	★ 8 4880 25 08	200
red matt	★ 8 4880 25 07	200
green matt	★ 8 4880 25 03	200
orange matt	★ 8 4880 25 04	200



for installation wall thickness 2 mm (+0.1/-0.3 mm)

anthracite matt	★ 8 4870 25 15	200
polar white matt	★ 8 4870 25 12	200
red matt	★ 8 4870 25 17	200
green matt	★ 8 4870 25 13	200
orange matt	★ 8 4870 25 14	200

for installation wall thickness 3 mm (+0.1/-0.3 mm)

anthracite matt	★ 8 4880 25 15	200
polar white matt	★ 8 4880 25 12	200
red matt	★ 8 4880 25 17	200
green matt	★ 8 4880 25 13	200
orange matt	★ 8 4880 25 14	200

New



SCHUKO socket outlet 45° with control LED, SNAP IN

▶ 212

- enhanced contact protection
- insulation-piercing terminals



Rated voltage	250 V~
Rated current	16 A
LED current	1 mA
Conductor cross-section (flexible)	2.5 mm²

- with green control LED as function light
- with distance sealing ring
- for diagonal installation

Suitable for	Order no.	Page
Optional		
Frame with hinged cover and imprint "IP44"		upon request

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

Design	Order no.	PU
--------	-----------	----

for installation wall thickness 1 mm (± 0.1 mm)

anthracite matt	★ 8 4861 25 15	200
polar white matt	★ 8 4861 25 12	200
red matt	★ 8 4861 25 17	200
green matt	★ 8 4861 25 13	200
orange matt	★ 8 4861 25 14	200

for installation wall thickness 2 mm (+0.1/-0.3 mm)

anthracite matt	★ 8 4871 25 15	200
polar white matt	★ 8 4871 25 12	200
red matt	★ 8 4871 25 17	200
green matt	★ 8 4871 25 13	200
orange matt	★ 8 4871 25 14	200

for installation wall thickness 3 mm (+0.1/-0.3 mm)

anthracite matt	★ 8 4881 25 15	200
polar white matt	★ 8 4881 25 12	200
red matt	★ 8 4881 25 17	200
green matt	★ 8 4881 25 13	200
orange matt	★ 8 4881 25 14	200



Socket outlets with earthing contact

NEMA-socket outlets



Socket outlet with earthing contact USA/CANADA NEMA 5-15 R

▶ 210

- screw terminals

- 2pole + earth



Rated voltage

125 V~

Rated current

15 A

Suitable for

Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 1820 ..
9 188 ..
9 191 ..
9 1933

Page

63
63
63
64

Connecting terminals only suitable for wiring with massive conductors.

Insert, UL-certified: E140596

Standard NEMA 5-15 R

Design

Order no.

PU

brown matt, insert brown

8 6263 25 01

200

polar white matt, insert white

8 6263 25 02

200

black matt, insert black

8 6263 25 13

200

brown matt, insert brown

9 6263 25 01

10

polar white matt, insert white

9 6263 25 02

10

black matt, insert black

9 6263 25 13

10



Socket outlet with earthing contact USA/CANADA NEMA 6-20 R

▶ 210

- screw terminals

- 2pole + earth



Rated voltage

250 V~

Rated current

20 A

Suitable for

Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 1820 ..
9 188 ..
9 191 ..
9 1933

Page

63
63
63
64

Connecting terminals only suitable for wiring with massive conductors.

Insert, UL-certified: E140596

Standard NEMA 6-20 R

Design

Order no.

PU

brown matt, insert brown

8 6254 25 01

200

anthracite matt, insert brown

8 6254 25 05

200

grey glossy, insert white

8 6254 25 07

200

polar white glossy, insert white

8 6254 25 09

200

black glossy, insert brown

8 6254 25 10

200

brown matt, insert brown

9 6254 25 01

10

grey glossy, insert white

9 6254 25 07

10

polar white glossy, insert white

9 6254 25 09

10

black glossy, insert brown

9 6254 25 10

10



Australian socket outlets



Socket outlet with earthing contact AUSTRALIA 10 A

▶ 210

- screw terminals

- 2pole + earth



Rated voltage

250 V~

Rated current

10 A

Suitable for

Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 1820 ..
9 188 ..
9 191 ..
9 1933

Page

63
63
63
64

Design

Order no.

PU

brown matt, insert black

9 6258 25 01

10

anthracite matt, insert black

9 6258 25 05

10

grey matt, insert black

9 6258 25 06

10

polar white matt, insert white

9 6258 25 02

10

black matt, insert black

9 6258 05

10





Socket outlet with earthing contact AUSTRALIA 15 A

▶ 210

- screw terminals

- 2pole + earth



Rated voltage

250 V~

Rated current

15 A

Suitable for

Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 1820 ..
9 188 ..
9 191 ..
9 1933

Page

63
63
63
64

Design

Order no.

PU

brown matt, insert black

9 6256 25 01

10

anthracite matt, insert black

9 6256 25 05

10

grey matt, insert black

9 6256 25 06

10

polar white matt, insert white

9 6256 25 02

10

black matt, insert black

9 6256 05

10



Danish socket outlets



Socket outlet with earthing contact DENMARK

▶ 210

- enhanced contact protection

- 2pole + earth

- screw terminals



Rated voltage

250 V~

Rated current

13 A

Suitable for

Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 1820 ..
9 188 ..
9 191 ..
9 1933

Page

63
63
63
64

Standard DS 60884-2-D1:2011

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

Design

Order no.

PU

black matt

8 6272 05

200

anthracite matt

9 6272 25 05

10

grey matt

9 6272 25 06

10

polar white matt

9 6272 25 02

10

black matt

9 6272 05

10



Italian socket outlets



Socket outlet with earthing contact ITALY

▶ 210

- enhanced contact protection

- 2pole + earth

- screw terminals



Rated voltage

250 V~

Rated current

16 A

Suitable for

Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 188 ..
9 1915 0 ..
9 1933

Page

63
63
64

Not suitable for fixing clamping ring!

Enhanced contact protection (child protection) according to IEC 60884-1

Design

Order no.

PU

anthracite matt, insert black

9 6251 25 05

10

polar white matt, insert white

9 6251 25 02

10

black matt, insert black

9 6251 25 03

10



Swiss socket outlets



Socket outlet with earthing contact SWITZERLAND type 13

▶ 210

- screw terminals

- 2pole + earth



Rated voltage

250 V~

Rated current

10 A

Suitable for

Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 188 ..
9 1915 0 ..
9 1933

Page

63
63
64

Not suitable for fixing clamping ring!

Connection terminals according to IEC 60884-1

Design	Order no.	PU
brown matt	8 6249 25 01	200
anthracite matt	8 6249 25 05	200
polar white matt	8 6249 25 02	200
black matt	8 6249 05	200
brown matt	9 6249 25 01	10
anthracite matt	9 6249 25 05	10
grey matt	9 6249 25 06	10
polar white matt	9 6249 25 02	10
black matt	9 6249 05	10



Socket outlet with earthing contact SWITZERLAND type 23

▶ 210

- screw terminals

- 2pole + earth



Rated voltage

250 V~

Rated current

16 A

Suitable for

Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 188 ..
9 1915 0 ..
9 1933

Page

63
63
64

Not suitable for fixing clamping ring!

Connection terminals according to IEC 60884-1

Design	Order no.	PU
brown matt	9 6259 25 01	10
anthracite matt	9 6259 25 05	10
grey matt	9 6259 25 06	10
polar white matt	9 6259 25 02	10
black matt	9 6259 25 03	10



British Standard socket outlets



Socket outlet with earthing contact BRITISH STANDARD

▶ 210

- enhanced contact protection
- screw terminals

- 2pole + earth



Rated voltage

250 V~

Rated current

13 A

Suitable for

Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 1820 ..
9 188 ..
9 191 ..
9 1933

Page

63
63
63
64

Standard BS 1363

Design	Order no.	PU
anthracite matt	8 6262 25 05	200
grey matt	8 6262 25 06	200
polar white matt	8 6262 25 02	200
black matt	8 6262 05	200
brown matt	9 6262 25 01	10
anthracite matt	9 6262 25 05	10
grey matt	9 6262 25 06	10
polar white matt	9 6262 25 02	10
black matt	9 6262 05	10



Socket outlets with earthing pin

– for 4-hole screw fitting

Socket outlets with earthing pin and screw terminals



Marked items are only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing (order no. 9 1853), frame with hinged cover and imprint "IP44" and contact protection box.



Socket outlet with earthing pin

▶ 210



– screw terminals



Rated voltage

250 V~

Rated current

16 A

Connection terminals according to IEC 60884-1

– 2pole + earth

Suitable for

Contact protection box Ø 45 mm

Order no.

9 1820 ..

Page

63

Contact protection box Ø 49 mm

9 188 ..

63

Contact protection box 2gang

9 191 ..

63

Contact protection box 3gang

9 1933

64

Optional

Sealing for IP44 applications

9 1853

78

Frame with hinged cover and imprint "IP44"

8 1828 ..

77

Design

Order no.

PU

brown matt

8 6185 25 01

200

anthracite matt

8 6185 25 05

200

polar white matt

8 6185 25 02

200

black matt

8 6185 05

200

brown matt

9 6185 25 01

10

anthracite matt

9 6185 25 05

10

grey matt

9 6185 25 06

10

polar white matt

9 6185 25 02

10

black matt

9 6185 05

10



Socket outlet with earthing pin

▶ 210



– enhanced contact protection

– screw terminals



Rated voltage

250 V~

Rated current

16 A

Connection terminals according to IEC 60884-1

– 2pole + earth

Suitable for

Contact protection box Ø 45 mm

Order no.

9 1820 ..

Page

63

Contact protection box Ø 49 mm

9 188 ..

63

Contact protection box 2gang

9 191 ..

63

Contact protection box 3gang

9 1933

64

Optional

Sealing for IP44 applications

9 1853

78

Frame with hinged cover and imprint "IP44"

8 1828 ..

77

Enhanced contact protection (child protection) according to IEC 60884-1

Design

Order no.

PU

anthracite matt

8 6195 25 05

200

grey matt

8 6195 25 06

200

polar white matt

8 6195 25 02

200

black matt

8 6195 05

200

brown matt

9 6195 25 01

10

anthracite matt

9 6195 25 05

10

grey matt

9 6195 25 06

10

polar white matt

9 6195 25 02

10

black matt

9 6195 05

10



Socket outlets with earthing pin and insulation-piercing terminals

- New: Insulation-piercing terminals (IPT) for quick and easy connection with the joining tool, order no. 8 1726 25 81
- VDE approval
- Up to 2 flexible conductors with a cross section of 2.5 mm² can be connected for each IPT contact; wires do not have to be stripped in advance.
- Enables multiple socket outlets to be looped through without breaking the conductors.
- IPT contacts made from copper alloy, tin-plated
- thermoplastic centre plates and bases
- Base with snap-on safety cap

Marked items are only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing (order no. 9 1853 01) and frame with hinged cover and imprint "IP44".

New		Socket outlet with earthing pin		212
		- enhanced contact protection - insulation-piercing terminals	- 2pole + earth	
			Suitable for Optional Sealing IP44 for socket outlets with insulation displacement contacts Frame with hinged cover and imprint "IP44"	Order no. 9 1853 01 8 1828 ..
		 		Page
		Rated voltage	250 V~	
		Rated current	16 A	
		Conductor cross-section (flexible)	2.5 mm ²	
		Earth bracket clamping forces according to TNO requirements. Not suitable for contact protection boxes (cavity walls). Connection terminals according to IEC 60884-1 Enhanced contact protection (child protection) according to IEC 60884-1		
		Design	Order no.	PU
		anthracite matt	★ 8 6301 25 05	200
		polar white matt	★ 8 6301 25 02	200
		red matt	★ 8 6301 25 07	200
		green matt	★ 8 6301 25 03	200
		orange matt	★ 8 6301 25 04	200



New		Socket outlet with earthing pin and control LED		212
		- enhanced contact protection - insulation-piercing terminals	- with green control LED as function light - 2pole + earth	
			Suitable for Optional Frame with hinged cover and imprint "IP44" Sealing IP44 for socket outlets with insulation displacement contacts	Order no. 9 1853 01
		 		Page
		Rated voltage	250 V~	
		Rated current	16 A	
		LED current	1 mA	
		Conductor cross-section (flexible)	2.5 mm ²	
		Earth bracket clamping forces according to TNO requirements. Not suitable for contact protection boxes (cavity walls). Connection terminals according to IEC 60884-1 Enhanced contact protection (child protection) according to IEC 60884-1		
		Design	Order no.	PU
		anthracite matt	★ 8 6301 25 15	200
		grey matt	★ 8 6301 25 16	200
		polar white matt	★ 8 6301 25 12	200
		black matt	★ 8 6301 25 18	200
		red matt	★ 8 6301 25 17	200
		green matt	★ 8 6301 25 13	200
		orange matt	★ 8 6301 25 14	200





Socket outlet with earthing pin 45°

- enhanced contact protection
- insulation-piercing terminals



Rated voltage	250 V~
Rated current	16 A
Conductor cross-section (flexible)	2.5 mm²

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

- for diagonal installation
- 2pole + earth

Suitable for	Order no.	Page
Optional		
Sealing IP44 for socket outlets with insulation displacement contacts	9 1853 01	79
Frame with hinged cover and imprint "IP44"	8 1828 ..	77

Design	Order no.	PU
anthracite matt	★ 8 6351 25 05	200
polar white matt	★ 8 6351 25 02	200
red matt	★ 8 6351 25 07	200
green matt	★ 8 6351 25 03	200
orange matt	★ 8 6351 25 04	200



Socket outlet with earthing pin 45° and control LED

- enhanced contact protection
- insulation-piercing terminals



Rated voltage	250 V~
Rated current	16 A
LED current	1 mA
Conductor cross-section (flexible)	2.5 mm²

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

- with green control LED as function light
- for diagonal installation
- 2pole + earth

Suitable for	Order no.	Page
Optional		
Frame with hinged cover and imprint "IP44"		upon request
Sealing IP44 for socket outlets with insulation displacement contacts	9 1853 01	79

Design	Order no.	PU
anthracite matt	★ 8 6351 25 15	200
grey matt	★ 8 6351 25 16	200
polar white matt	★ 8 6351 25 12	200
black matt	★ 8 6351 25 18	200
red matt	★ 8 6351 25 17	200
green matt	★ 8 6351 25 13	200
orange matt	★ 8 6351 25 14	200



Socket outlets without earthing contact

- for 4-hole screw fitting

Dutch socket outlets



Socket outlet without earth contact NETHERLANDS

▶ 210

- enhanced contact protection
- screw terminals



Rated voltage 250 V~
Rated current 16 A
Mirror depth 14.5 mm

Connection terminals according to IEC 60884-1
Enhanced contact protection (child protection) according to IEC 60884-1

- 2pole

Suitable for

Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 182 ..
9 188 ..
9 191 ..
9 1933

Page

63
63
63
64

Design	Order no.	PU
anthracite matt	9 6194 25 05	10
grey matt	9 6194 25 06	10
polar white matt	9 6194 25 02	10
black matt	9 6194 05	10



Euro-American Standard socket outlets



Socket outlet without earthing contact EURO-AMERICAN STANDARD

▶ 210

- enhanced contact protection
- screw terminals



Rated voltage 250 V~
Rated current 10 A

Not suitable for SCHUKO plug according to DIN 49441.
Standard GB 1002

Connection terminals according to IEC 60884-1
Enhanced contact protection (child protection) according to IEC 60884-1

- 2pole

Suitable for

Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 1820 ..
9 188 ..
9 191 ..
9 1933

Page

63
63
63
64

Design	Order no.	PU
anthracite matt	8 6257 25 05	200
polar white matt	8 6257 25 02	200
brown matt	9 6257 25 01	10
anthracite matt	9 6257 25 05	10
grey matt	9 6257 25 06	10
polar white matt	9 6257 25 02	10
black matt	9 6257 25 03	10



Connecting devices 12 V



Socket outlet 12 V

Operating voltage	12 ... 24 V
Rated current	max. 16 A
Flat connector size (size width x size width)	6.3 x 0.8 mm
Installation depth (without cable lug)	30 mm

– with fast-on terminal connection

Note:
When using 12 V connector (order no. 4637), observe
max. rated current of 8 A.
DIN EN ISO 4165

Suitable for	Order no.	Page
Contact protection box Ø 45 mm	9 1820 ..	63
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 191 ..	63
Contact protection box 3gang	9 1933	64
Plug 12 V	4637	66

Design	Order no.	PU
brown matt	8 4517 25 01	200
anthracite matt	8 4517 25 05	200
grey glossy	8 4517 25 07	200
polar white glossy	8 4517 25 09	200
brown matt	9 4517 25 01	10
anthracite matt	9 4517 25 05	10
grey glossy	9 4517 25 07	10
polar white glossy	9 4517 25 09	10
black matt	9 4517 05	10



Power socket outlet 12 V

Operating voltage	12 ... 24 V
Rated current for 1.5 mm ²	max. 15 A
Rated current for 2.5 mm ²	max. 20 A
Flat connector size (size width x size width)	6.3 x 0.8 mm
Installation depth (without cable lug)	46 mm

– with fast-on terminal connection

Not suitable for contact protection boxes (cavity walls).

Not suitable for installation in surface-mounted housing.
Compliant with SAE J563 (Feb. 2009), VW Standard
TL82285 (Apr. 2007)

Design	Order no.	PU
brown matt	8 4571 25 01	200
anthracite matt	8 4571 25 05	200
grey glossy	8 4571 25 07	200
polar white glossy	8 4571 25 09	200
black matt	8 4571 25 03	200
brown matt	9 4571 25 01	10
anthracite matt	9 4571 25 05	10
grey glossy	9 4571 25 07	10
polar white glossy	9 4571 25 09	10



Power socket outlet 12 V, with imprint 20 A for motor vehicles

Operating voltage	12 ... 24 V
Rated current for 1.5 mm ²	max. 15 A
Rated current for 2.5 mm ²	max. 20 A
Flat connector size (size width x size width)	6.3 x 0.8 mm
Installation depth (without cable lug)	46 mm

– with fast-on terminal connection

Not suitable for contact protection boxes (cavity walls).

Not suitable for installation in surface-mounted housing.

Design	Order no.	PU
anthracite matt	9 4570 25 05	10





Power socket outlet 12 V, with imprint 10 A for motor vehicles

Operating voltage	12 ... 24 V	- with fast-on terminal connection
Rated current	max. 10 A	
Flat connector size (size width x size width)	6.3 x 0.8 mm	
Installation depth (without cable lug)	46 mm	

Not suitable for contact protection boxes (cavity walls).

Not suitable for installation in surface-mounted housing.



Design	Order no.	PU
anthracite matt	9 4570 25 15	10



Socket outlet 12 V + SAT

Operating voltage	12 V=	- with double F-socket
Rated current	max. 10 A	- with fast-on terminal connection
Installation depth (without cable lug)	28 mm	

Not suitable for frames with hinged covers.

For reception of satellite TV signals and simultaneous power supply of appropriate TV devices.



Design	Order no.	PU
brown matt	8 4572 25 01	200
anthracite matt	8 4572 25 05	200
polar white matt	8 4572 25 02	200
black matt	8 4572 25 03	200
brown matt	9 4572 25 01	10
anthracite matt	9 4572 25 05	10
polar white matt	9 4572 25 02	10
black matt	9 4572 25 03	10



Socket outlet 12 V + TV

Operating voltage	12 V=	- with IEC jack (male), connection in F system on the rear
Rated current	max. 10 A	- with fast-on terminal connection
Installation depth (without cable lug)	28 mm	

For reception of terrestrial or wire-connected TV signals with simultaneous power supply of appropriate devices.

Not suitable for frames with hinged covers.



Design	Order no.	PU
anthracite matt	9 4573 25 05	10
polar white matt	9 4573 25 02	10



Socket outlet 12 V + Radio

Operating voltage	12 V=	- with IEC jack (female), connection in F system on the rear
Rated current	max. 10 A	- with fast-on terminal connection
Installation depth (without cable lug)	28 mm	

For reception of terrestrial or wire-connected radio signals with simultaneous power supply of appropriate devices.

In some countries, this insert can also be used for TV reception.

Not suitable for frames with hinged covers.



Design	Order no.	PU
anthracite matt	9 4574 25 05	10
polar white matt	9 4574 25 02	10

USB charging sockets

- for charging mobile end devices via USB cable
- short-circuit and overload proof (electronic fuse)

New



USB charging socket 2gang 230 V, 3 A

- screw terminals



Frequency	50/60 Hz
Output voltage	5 V= (± 5 %)
Output current per socket	max. 3 A
Output current when operating both sockets	max. 3 A
Power consumption (standby)	max. 150 mW
Conductor cross-section (rigid)	max. 2.5 mm ²
Installation depth	31 mm

No data transmission possible!

- with 2 USB sockets type A

Suitable for	Order no.	Page
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 1915 0 ..	63
Contact protection box 3gang	9 1933	64



Design	Order no.	PU
anthracite matt	★ 9 2610 25 05	1
polar white matt	★ 9 2610 25 09	1

New



12 V USB charging socket outlet

Input voltage	8 ... 34 V=	– with USB socket type A
Output voltage	5 V= (± 5 %)	– pre-assembled with connecting cables (red, black), length approx. 15 cm
Output current	max. 3 A	
Power consumption (standby)	< 100 mW	
Installation depth	32 mm	

No data transmission possible!

Suitable for	Order no.	Page
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 1915 0 ..	63
Contact protection box 3gang	9 1933	64



Design	Order no.	PU
brown matt, insert black	★ 8 2603 25 01	200
anthracite matt, insert black	★ 8 2603 25 05	200
grey glossy, insert black	★ 8 2603 25 07	200
polar white glossy, insert black	★ 8 2603 25 09	200
black matt, insert black	★ 8 2603 25 03	200
brown matt, insert black	★ 9 2603 25 01	10
anthracite matt, insert black	★ 9 2603 25 05	10
grey glossy, insert black	★ 9 2603 25 07	10
polar white glossy, insert black	★ 9 2603 25 09	10
black matt, insert black	★ 9 2603 25 03	10



12 V USB charging socket outlet 2gang

Input voltage	8 ... 34 V=	– with 2 USB sockets type
Output voltage	5 V= (± 5 %)	– pre-assembled with connecting cables (red, black), length approx. 15 cm
Output current per socket	max. 2.5 A	
Output current when operating both sockets	max. 5 A	
Power consumption (standby)	< 100 mW	
Installation depth	32 mm	

Suitable for	Order no.	Page
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 1915 0 ..	63
Contact protection box 3gang	9 1933	64

No data transmission possible!

Design	Order no.	PU
brown matt, insert black	8 2602 25 01	200
anthracite matt, insert black	8 2602 25 05	200
grey glossy, insert black	8 2602 25 07	200
polar white glossy, insert black	8 2602 25 09	200
black matt, insert black	8 2602 25 03	200
brown matt, insert black	9 2602 25 01	10
anthracite matt, insert black	9 2602 25 05	10
grey glossy, insert black	9 2602 25 07	10
polar white glossy, insert black	9 2602 25 09	10
black matt, insert black	9 2602 25 03	10



TV/multimedia

Aerial sockets



Aerial connector box TV

DIN 45325	– with IEC jack (male)
	– for soldered connection

Suitable for	Order no.	Page
Frame with hinged cover	9 1828 ..	76

Design	Order no.	PU
brown matt	9 4511 25 11	10
anthracite matt	9 4511 25 15	10
polar white matt	9 4511 25 12	10
black matt	9 4511 15	10



Aerial connector box TV

Not suitable for frames with hinged covers.	– with IEC jack (male)
DIN 45325	– connection in F system on the rear

Design	Order no.	PU
brown matt	9 4581 25 01	10
anthracite matt	9 4581 25 05	10
grey matt	9 4581 25 06	10
polar white matt	9 4581 25 02	10
black matt	9 4581 25 03	10



Aerial connector box radio

Not suitable for frames with hinged covers.	– with IEC jack (female)
	– connection in F system on the rear

Design	Order no.	PU
anthracite matt	9 4562 25 05	10





Aerial connector box SAT

Not suitable for frames with hinged covers.

- with double F-socket

Design	Order no.	PU
anthracite matt	8 4519 25 05	200
polar white matt	8 4519 25 02	200
brown matt	9 4519 25 01	10
anthracite matt	9 4519 25 05	10
grey matt	9 4519 25 06	10
polar white matt	9 4519 25 02	10
black matt	9 4519 05	10



Aerial connector box radio/SAT

Not suitable for frames with hinged covers.

- with IEC and F socket
- connection in F system on the rear

Design	Order no.	PU
brown matt	9 4560 25 01	10
anthracite matt	9 4560 25 05	10
grey matt	9 4560 25 06	10
polar white matt	9 4560 25 02	10
black matt	9 4560 05	10



Aerial connector box radio/TV

Not suitable for frames with hinged covers.

- with IEC jacks (male/female)
- connection in F system on the rear

Design	Order no.	PU
polar white matt	9 4561 25 02	10



Aerial connector box TV/SAT

Not suitable for frames with hinged covers.

- with IEC and F socket
- connection in F system on the rear

Design	Order no.	PU
grey matt	8 4563 25 06	200
black matt	8 4563 25 03	200



Multimedia outlets



USB/3.5 mm audio socket outlet

Frequency range audio	20 ... 20000 Hz	- double jack gold-plated 3.5 mm, stereo
USB transmission rate	max. 480 Mbit/s	- with USB, double socket type A, USB 2.0 compatible

For connecting mobile devices, such as mobile phones or MP3 players (mini audio), digital cameras and computer peripherals (USB 2.0).

Observe the instructions of the cable and device manufacturers for maximum USB cable lengths!

Design	Order no.	PU
brown matt	8 4583 25 01	200
anthracite matt	8 4583 25 05	200
grey matt	8 4583 25 06	200
polar white matt	8 4583 25 02	200
black matt	8 4583 25 03	200
brown matt	9 4583 25 01	10
anthracite matt	9 4583 25 05	10
grey matt	9 4583 25 06	10
polar white matt	9 4583 25 02	10
black matt	9 4583 25 03	10



High definition socket outlet

Resolution	max. 1920 x 1080 px	- with HDMI™ double jack type A, supports HDMI™ technology (V 1.3 with Deep Color)
Transmission rate	max. 8.16 GBit/s	- 19pole
Video bandwidth	max. 165 MHz	- gold-plated contacts
Frequency range (vertical)	50 ... 85 Hz	

For the connection of digital devices for transmission of high-resolution audio and video signals, such as satellite receivers and DVD players, to LCD or LED screens.

Comply with the instructions of the cable and device manufacturers as to the maximum HDMI cable length.

Design	Order no.	PU
brown matt	8 4582 25 01	200
anthracite matt	8 4582 25 05	200
grey matt	8 4582 25 06	200
polar white matt	8 4582 25 02	200
black matt	8 4582 25 03	200
brown matt	9 4582 25 01	10
anthracite matt	9 4582 25 05	10
grey matt	9 4582 25 06	10
polar white matt	9 4582 25 02	10
black matt	9 4582 25 03	10



Cinch socket outlet 3-gang

Not suitable for frames with hinged covers.

- 1 cinch double jack for video connection (yellow)
- 2 cinch double jacks for audio connection (red, white)

Design	Order no.	PU
brown matt	8 4580 25 01	200
anthracite matt	8 4580 25 05	200
grey matt	8 4580 25 07	200
polar white matt	8 4580 25 09	200
black matt	8 4580 25 03	200



Audio/video modules



Cinch module set audio

Conductor Ø 0.5 ... 0.65 mm (AWG 24-22)
Conductor cross-section 0.2 mm² ... 0.325 mm²
Dimensions, per module (W x H x D) 15 x 18 x 35 mm

- with 2 Cinch sockets and module carriers
- with tool free cutting terminals

Suitable for Double supporting plate for MINI-COM modules
Order no. 9 4559 ..

211

Page 52



Design

polar white/red

Order no.

1989

PU

1



Cinch module video

Conductor Ø 0.5 ... 0.65 mm (AWG 24-22)
Conductor cross-section 0.2 mm² ... 0.325 mm²
Dimensions (W x H x D) 15 x 18 x 35 mm

- with cinch socket and module carrier
- with tool free cutting terminals

Suitable for Double supporting plate for MINI-COM modules
Order no. 9 4559 ..

211

Page 52



Design

polar white/yellow

Order no.

1992

PU

1



VGA module

Conductor cross-section 1.5 mm²
Dimensions (W x H x D) 31 x 18 x 35 mm

- with a 15pole D-subminiature socket
- occupies 2 MINI-COM module spaces in the cover
- SVGA compatible
- with screw-in lift terminals

Suitable for Double supporting plate for MINI-COM modules
Order no. 9 4559 ..

211

Page 52



Design

polar white/black

Order no.

1994

PU

1



S-Video module

Conductor Ø 0.5 ... 0.65 mm (AWG 24-22)
Conductor cross-section 0.2 mm² ... 0.325 mm²
Dimensions (W x H x D) 15 x 18 x 35 mm

- with S-Video and module carrier
- with tool free cutting terminals

Suitable for Double supporting plate for MINI-COM modules
Order no. 9 4559 ..

213

Page 52



Design

polar white/black

Order no.

1993

PU

1



Blank module

Dimensions (W x H x D) 15 x 18 x 35 mm

Suitable for Double supporting plate for MINI-COM modules
Order no. 9 4559 ..

Page 52

Design

polar white

Order no.

1990

PU

1

Data communication

Supporting plates for modular jacks



Double supporting plate for MINI-COM modules

Not suitable for frames with hinged covers.

- for Mini-Com 3.5 mm stereo connection/coupling modules
- for Mini-Com BNC connector modules
- for Mini-Com Cinch connection/coupling modules
- for Mini-Com D-Subminiature connectors 15pole
- for Mini-Com F-plug coupling modules
- for Mini-Com speaker wire/banana plug modules
- for Mini-Com S-Video connection/coupling modules
- for Mini-Com jacks Cat.3, Cat.5e, Cat.6, Cat.6 10Gig
- for Mini-Com fibre-optic modules
- for Mini-Com dummy modules 1gang
- with 30° oblique outlet

Suitable for
Audio/video modules
Modular Jacks

Order no.

Page
from p. 51
from p. 53

Manufacturer product line
Mini-Com modules
Panduit

Art. no.

Design	Order no.	PU
anthracite glossy	9 4559 25 05	10
grey glossy	9 4559 25 07	10
polar white glossy	9 4559 25 09	10
black glossy	9 4559 05	10



Supporting plate 1gang for AMP modular jacks

Indexing dimension (W x H) ≈ 14.9 x 20.7 mm

Not suitable for frames with hinged covers.

- for AMP modular jacks series 110 Connect, Cat.3, Cat.5, Cat.5e and Cat.6

Manufacturer product line
EMT modular jack
AMP
Standard 110 Connect jack
AMP
MT-RJ jack
AMP
Intracom
Telena
Modular jacks
Brand-Rex
CobiNet
EFB Electronic
Schumann
SL series toolless jack
AMP

Art. no.

Design	Order no.	PU
anthracite glossy	9 4557 25 05	10
grey glossy	9 4557 25 07	10
polar white glossy	9 4557 25 09	10
black glossy	9 4557 05	10



Supporting plate 2gang for BTR-/E-DAT modules

Not suitable for frames with hinged covers.

- for 130898-00-I BTR blank module
- for 130898-01-I BTR coax module F/F
- for 130898-02-I BTR coax module F/IEC socket
- for 130898-03-I BTR coax module F/IEC connector
- for 130908-I BTR FCC module Cat.5e 8(8)
- for 130909-I BTR FCC module Cat.6 8(8)
- for 130910-I BTR E-Dat module Cat.6a 8(8)
- for 1309A0-I BTR E-Dat module coupling 8(8) Cat.6
- for 15091001-I BTR Op-Dat module ST
- for 15091070-I BTR Op-Dat module LC
- for 15091071-I BTR Op-Dat module LC
- for 185700 Dätwyler Unilan socket module MS 1/8 Cat.6
- for 185750 Dätwyler Unilan socket module MU 1/8 Cat.6
- for 417446 Dätwyler Unilan RJ45 feed-through coupling
- with 25° oblique outlet

Manufacturer product line

Art. no.

Modules
BTR NETCOM

Design	Order no.	PU
anthracite glossy	8 4558 25 05	100
grey glossy	8 4558 25 07	100
polar white glossy	8 4558 25 09	100
black glossy	8 4558 25 10	100

Modular Jacks



Mini jack, 8-pole

Colour code A and B according to TIA/EIA-568-B.2

Cat.5e according to ISO/IEC 11801

Cat.6 according to ISO/IEC 11801, 2nd edition

- with cutting terminals

Suitable for

Double supporting plate for MINI-COM modules

Order no.

9 4559 ..

Page

52

Design	Order no.	PU
black, RJ45, Cat.3, ISDN-compatible (AWG 24-22)	1980	1
Aluminium, RJ45, Cat.5e, shielded (AWG 24-22)	1984	1
Aluminium, RJ45, Cat.6, shielded (AWG 26)	1985	1



Rocker switch

 Marked items are only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing (order no. 9 1853), frame with imprint "IP44" and contact protection box.



On/off switch

Rated voltage
Switching current

250 V~
16 AX – with screw terminals

▶ 211

Suitable for	Order no.	Page
Contact protection box Ø 45 mm, flat	9 1820 0 ..	63
Contact protection box Ø 45 mm	9 1820 ..	63
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 191 ..	63
Contact protection box 3gang	9 1933	64
Optional		
Sealing for IP44 applications	9 1853	78
Frame with imprint "IP44"	9 1827 ..	77

Design

Order no.

PU

Berker Integro - Design Flow/Pure

brown matt	8 3651 25 01	200
anthracite matt	8 3651 25 05	200
grey glossy	8 3651 25 07	200
polar white glossy	8 3651 25 09	200

brown matt	9 3651 25 01	10
anthracite matt	9 3651 25 05	10
grey glossy	9 3651 25 07	10
polar white glossy	9 3651 25 09	10
black glossy	9 3651 25 10	10
granite black, silk matt, lacquered	9 3651 25 45	10
chrome glossy, galvanised	9 3651 25 18	10
chrome matt, galvanised	9 3651 25 28	10
chrome matt, lacquered	9 3651 25 68	10
stainless steel matt, lacquered	9 3651 25 24	10

Berker Integro - Design Classic

polar white glossy	8 3651 09	200
black matt	8 3651 05	200

brown matt	9 3651 01	10
grey glossy	9 3651 07	10
polar white glossy	9 3651 09	10
black matt	9 3651 05	10
granite black, silk matt, lacquered	9 3651 45	10
chrome glossy, galvanised	9 3651 18	10
chrome matt, galvanised	9 3651 28	10
gold glossy, galvanised	9 3651 38	10





Change-over switch

Rated voltage
Switching current

250 V~
16 AX – with screw terminals

▶ 211

Suitable for	Order no.	Page
Contact protection box Ø 45 mm, flat	9 1820 0 ..	63
Contact protection box Ø 45 mm	9 1820 ..	63
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 191 ..	63
Contact protection box 3gang	9 1933	64
Optional		
Sealing for IP44 applications	9 1853	78
Frame with imprint "IP44"	9 1827 ..	77

Design

Order no.

PU

Berker Integro - Design Flow/Pure

anthracite matt	8 3656 25 05	200
grey glossy	8 3656 25 07	200
polar white glossy	8 3656 25 09	200

brown matt	9 3656 25 01	10
anthracite matt	9 3656 25 05	10
grey glossy	9 3656 25 07	10
polar white glossy	9 3656 25 09	10
black glossy	9 3656 25 10	10
granite black, silk matt, lacquered	9 3656 25 45	10
chrome glossy, galvanised	9 3656 25 18	10
chrome matt, galvanised	9 3656 25 28	10
chrome matt, lacquered	9 3656 25 68	10
Stainless steel matt, lacquered	9 3656 25 24	10
gold glossy, galvanised	9 3656 25 38	10

Berker Integro - Design Classic

polar white glossy	8 3656 09	200
brown matt	9 3656 01	10
grey glossy	9 3656 07	10
polar white glossy	9 3656 09	10
black matt	9 3656 05	10
granite black, silk matt, lacquered	9 3656 45	10
chrome glossy, galvanised	9 3656 18	10
chrome matt, galvanised	9 3656 28	10



Intermediate switch

Rated voltage
Switching current

250 V~
16 AX – with screw terminals

▶ 211

Suitable for	Order no.	Page
Contact protection box Ø 45 mm, flat	9 1820 0 ..	63
Contact protection box Ø 45 mm	9 1820 ..	63
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 191 ..	63
Contact protection box 3gang	9 1933	64
Optional		
Sealing for IP44 applications	9 1853	78
Frame with imprint "IP44"	9 1827 ..	77

Design

Order no.

PU

Berker Integro - Design Flow/Pure

brown matt	9 3657 25 01	10
anthracite matt	9 3657 25 05	10
grey glossy	9 3657 25 07	10
polar white glossy	9 3657 25 09	10
black glossy	9 3657 25 10	10
chrome matt, galvanised	9 3657 25 28	10
chrome matt, lacquered	9 3657 25 68	10
Stainless steel matt, lacquered	9 3657 25 24	10

Berker Integro - Design Classic

brown matt	9 3657 01	10
polar white glossy	9 3657 09	10





On/off switch 2pole with imprint "0"

Rated voltage 250 V~
Switching current 16 AX

For switching of 16 A socket outlets, for example.

– with screw terminals

Suitable for	Order no.	Page
Contact protection box Ø 45 mm, flat	9 1820 0 ..	63
Contact protection box Ø 45 mm	9 1820 ..	63
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 191 ..	63
Contact protection box 3gang	9 1933	64
Optional		
Sealing for IP44 applications	9 1853	78
Frame with imprint "IP44"	9 1827 ..	77
Order no.		PU

Design

Berker Integro - Design Flow/Pure

polar white glossy 8 3652 25 09 200

brown matt 9 3652 25 01 10

anthracite matt 9 3652 25 05 10

grey glossy 9 3652 25 07 10

polar white glossy 9 3652 25 09 10

black glossy 9 3652 25 10 10

granite black, silk matt, lacquered 9 3652 25 45 10

chrome glossy, galvanised 9 3652 25 18 10

chrome matt, galvanised 9 3652 25 28 10

chrome matt, lacquered 9 3652 25 68 10

Stainless steel matt, lacquered 9 3652 25 24 10

Berker Integro - Design Classic

brown matt 9 3652 01 10

grey glossy 9 3652 07 10

polar white glossy 9 3652 09 10

black matt 9 3652 05 10

granite black, silk matt, lacquered 9 3652 45 10

chrome matt, galvanised 9 3652 28 10



Control on/off switch 2pole with imprint "0"

- red lens



Rated voltage 250 V~
Switching current 16 AX
Neon lamp current 0.9 mA

– for illumination and monitoring circuit
– with integral neon lamp
– with screw terminals

Suitable for	Order no.	Page
Contact protection box Ø 45 mm, flat	9 1820 0 ..	63
Contact protection box Ø 45 mm	9 1820 ..	63
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 191 ..	63
Contact protection box 3gang	9 1933	64
Optional		
Sealing for IP44 applications	9 1853	78
Frame with imprint "IP44"	9 1827 ..	77
Order no.		PU

Design

Berker Integro - Design Flow/Pure

anthracite matt 8 3752 25 05 200

chrome glossy, galvanised 8 3752 25 18 50

brown matt 9 3752 25 01 10

anthracite matt 9 3752 25 05 10

grey glossy 9 3752 25 07 10

polar white glossy 9 3752 25 09 10

black glossy 9 3752 25 10 10

chrome matt, lacquered 9 3752 25 68 10

Stainless steel matt, lacquered 9 3752 25 24 10

Berker Integro - Design Classic

black matt 8 3752 05 200

brown matt 9 3752 01 10

black matt 9 3752 05 10

grey glossy 9 3752 07 10


polar white glossy 9 3752 09 10





Control on/off switch 2pole with imprint "0", 12 V

- red lens
- control LED



Rated voltage

12 V=

Switching current

5 A

LED current

10 mA

- for illumination and monitoring circuit
- with integral indicator LED
- with screw terminals

Suitable for

Contact protection box Ø 45 mm, flat
Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 1820 0 ..
9 1820 ..
9 188 ..
9 191 ..
9 1933

Page

63
63
63
63
64

Optional

Sealing for IP44 applications
Frame with imprint "IP44"

9 1853
9 1827 ..

78
77

Design

Order no.

PU

Berker Integro - Design Flow/Pure

brown matt	9 3762 25 31	10
anthracite matt	9 3762 25 35	10
polar white glossy	9 3762 25 39	10
black glossy	9 3762 25 10	10
chrome glossy, galvanised	9 3762 25 18	10
chrome matt, lacquered	9 3762 25 68	10
Stainless steel matt, lacquered	9 3762 25 24	10



Multiple rocker switches



Series switch, common input terminal

Rated voltage

250 V~

Switching current

16 AX

- with screw terminals

Suitable for

Contact protection box Ø 45 mm, flat
Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 1820 0 ..
9 1820 ..
9 188 ..
9 191 ..
9 1933

Page

63
63
63
63
64

Design

Order no.

PU

Berker Integro - Design Flow/Pure

brown matt	8 3655 25 01	200
anthracite matt	8 3655 25 05	200
grey glossy	8 3655 25 07	200
polar white glossy	8 3655 25 09	200

brown matt	9 3655 25 01	10
anthracite matt	9 3655 25 05	10
grey glossy	9 3655 25 07	10
polar white glossy	9 3655 25 09	10
black glossy	9 3655 25 10	10
granite black, silk matt, lacquered	9 3655 25 45	10
chrome glossy, galvanised	9 3655 25 18	10
chrome matt, galvanised	9 3655 25 28	10
chrome matt, lacquered	9 3655 25 68	10
Stainless steel matt, lacquered	9 3655 25 24	10
gold glossy, galvanised	9 3655 25 38	10

Berker Integro - Design Classic

brown matt	9 3655 01	10
grey glossy	9 3655 07	10
polar white glossy	9 3655 09	10
black matt	9 3655 05	10
chrome glossy, galvanised	9 3655 18	10
chrome matt, galvanised	9 3655 28	10
gold glossy, galvanised	9 3655 38	10





Double on/off switch 12 V, isolated input terminals

Rated voltage
Switching current

12 V=
5 A

– with screw terminals

Suitable for

Contact protection box Ø 45 mm, flat
Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.
9 1820 0 ..
9 1820 ..
9 188 ..
9 191 ..
9 1933

Page
63
63
63
63
64

Design

Order no.

PU

Berker Integro - Design Flow/Pure

brown matt	8 3664 25 01	50
anthracite matt	8 3664 25 05	50
black glossy	8 3664 25 10	50
granite black, silk matt, lacquered	8 3664 25 45	50
chrome glossy, galvanised	8 3664 25 18	50
chrome matt, galvanised	8 3664 25 28	50
chrome matt, lacquered	8 3664 25 68	50



Rocker push-button

Marked items are only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing (order no. 9 1853), frame with imprint "IP44" and contact protection box.



Push-button, NO contact

Rated voltage
Momentary-contact current

250 V~
10 A

– with screw terminals

Suitable for

Contact protection box Ø 45 mm, flat
Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.
9 1820 0 ..
9 1820 ..
9 188 ..
9 191 ..
9 1933

Page
63
63
63
63
64

Optional

Sealing for IP44 applications
Frame with imprint "IP44"

9 1853
9 1827 ..

78
77

Design

Order no.

PU

Berker Integro - Design Flow/Pure

anthracite matt	8 3671 25 05	200
grey glossy	8 3671 25 07	200
brown matt	9 3671 25 01	10
anthracite matt	9 3671 25 05	10
grey glossy	9 3671 25 07	10
polar white glossy	9 3671 25 09	10
black glossy	9 3671 25 10	10
granite black, silk matt, lacquered	9 3671 25 45	10
chrome glossy, galvanised	9 3671 25 18	10
chrome matt, galvanised	9 3671 25 28	10
chrome matt, lacquered	9 3671 25 68	10
Stainless steel matt, lacquered	9 3671 25 24	10

Berker Integro - Design Classic

polar white glossy	8 3671 09	200
grey glossy	9 3671 07	10
polar white glossy	9 3671 09	10
black matt	9 3671 05	10
chrome glossy, galvanised	9 3671 18	10
chrome matt, galvanised	9 3671 28	10



Push-button, NO contact, illuminated



- red lens



Rated voltage	250 V~
Neon lamp current	0.9 mA
Momentary-contact current	10 A

When several neon lamp units are used, the lamp current may result in malfunctioning of the relay/pulse relay. Remedy: Carry along a neutral conductor or connect a capacitor 230 V (1 µF per 10 mA neon lamp current) in parallel with the coil.

- for illumination and monitoring circuit
- with integral neon lamp
- with screw terminals

Suitable for	Order no.	Page
Contact protection box Ø 45 mm, flat	9 1820 0 ..	63
Contact protection box Ø 45 mm	9 1820 ..	63
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 191 ..	63
Contact protection box 3gang	9 1933	64
Optional		
Sealing for IP44 applications	9 1853	78
Frame with imprint "IP44"	9 1827 ..	77

Design	Order no.	PU
Berker Integro - Design Flow/Pure		
brown matt	9 3772 25 01	10
anthracite matt	9 3772 25 05	10
grey glossy	9 3772 25 07	10
polar white glossy	9 3772 25 09	10

Multiple rocker push-buttons



Series push-button, 2 NO contacts, common input terminal

Rated voltage	250 V~
Momentary-contact current	10 A

- with screw terminals

Suitable for	Order no.	Page
Contact protection box Ø 45 mm	9 1820 ..	63
Contact protection box Ø 45 mm, flat	9 1820 0 ..	63
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 191 ..	63
Contact protection box 3gang	9 1933	64

Design	Order no.	PU
Berker Integro - Design Flow/Pure		
brown matt	9 3675 25 01	10
anthracite matt	9 3675 25 05	10
grey glossy	9 3675 25 07	10
polar white glossy	9 3675 25 09	10
black glossy	9 3675 25 10	10
granite black, silk matt, lacquered	9 3675 25 45	10
chrome glossy, galvanised	9 3675 25 18	10
chrome matt, galvanised	9 3675 25 08	10
chrome matt, lacquered	9 3675 25 68	10
Stainless steel matt, lacquered	9 3675 25 24	10

Berker Integro - Design Classic

brown matt	9 3675 01	10
grey glossy	9 3675 07	10
polar white glossy	9 3675 09	10
black matt	9 3675 05	10



Series push-button, isolated input terminals

Rated voltage	12 V=
Momentary-contact current	5 A

- with screw terminals

Suitable for	Order no.	Page
Contact protection box Ø 45 mm, flat	9 1820 ..	63
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 191 ..	63
Contact protection box 3gang	9 1933	64

Design	Order no.	PU
Berker Integro - Design Flow/Pure		
chrome glossy, galvanised	9 3665 25 18	10

Blind push-button



Blind series push-button with imprinted symbol arrow

Rated voltage

250 V~

– with electrical interlocking to prevent mutual activation

Momentary-contact current

10 A

– with screw terminals

Follow the motor manufacturers' instructions.

Suitable for

Contact protection box Ø 45 mm, flat
Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 1820 0 ..
9 1820 ..
9 188 ..
9 191 ..
9 1933

Page

63
63
63
63
64

Design

Order no.

PU

Berker Integro - Design Flow/Pure

brown matt

9 3653 25 01

10

anthracite matt

9 3653 25 05

10

grey glossy

9 3653 25 07

10

polar white glossy

9 3653 25 09

10

black glossy

9 3653 25 10

10

granite black, silk matt, lacquered

9 3653 25 45

10

chrome glossy, galvanised

9 3653 25 18

10

chrome matt, galvanised

9 3653 25 08

10

chrome matt, lacquered

9 3653 25 68

10

Stainless steel matt, lacquered

9 3653 25 24

10

Berker Integro - Design Classic

grey glossy

9 3653 07

10

polar white glossy

9 3653 09

10

black matt

9 3653 05

10



Reverse polarity push-button



Reverse polarity push-button, 6 contacts

Operating voltage

12 ... 24 V=

– double change-over contact, usable as NC or NO with separate input terminals

Flat connector size
(size width x size width)

4.8 x 0.8 mm

– 6 contacts at the backside

Momentary-contact current at 24 V=

7.5 A

– with fast-on terminal connection

Momentary-contact current at 12 V=

15 A

Suitable for

Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 1820 ..
9 188 ..
9 191 ..
9 1933

Page

63
63
63
64

Design

Order no.

PU

chrome glossy, galvanised

9 3697 25 18

10



Reverse polarity push-button, 4 contacts, with imprint for steps

Operating voltage

12 ... 24 V=

– e.g. for caravan step

Momentary-contact current at 12 V=

15 A

– 4 contacts at the backside

Momentary-contact current at 24 V=

7.5 A

– with fast-on terminal connection

Flat connector size
(size width x size width)

4.8 x 0.8 mm

Suitable for

Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 1820 ..
9 188 ..
9 191 ..
9 1933

Page

63
63
63
64

Design

Order no.

PU

anthracite matt

8 3699 25 05

200

brown matt

9 3699 25 01

10

anthracite matt

9 3699 25 05

10

grey glossy

9 3699 25 07

10

polar white glossy

9 3699 25 09

10

black glossy

9 3699 25 10

10

chrome matt, lacquered

9 3699 25 68

10

chrome matt, galvanised

9 3699 25 28

10



Reverse polarity push-button, 5 contacts, with imprint for steps

Operating voltage	12 ... 24 V=	- e.g. for caravan step
Momentary-contact current at 12 V=	15 A	- 5 contacts at the backside
Momentary-contact current at 24 V=	7.5 A	- with fast-on terminal connection
Flat connector size (size width x size width)	4.8 x 0.8 mm	

Suitable for	Order no.	Page
Contact protection box Ø 45 mm	9 1820 ..	63
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 191 ..	63
Contact protection box 3gang	9 1933	64

Design	Order no.	PU
stainless steel matt, lacquered	8 3695 25 24	200
brown matt	9 3695 25 01	10
anthracite matt	9 3695 25 05	10
grey glossy	9 3695 25 07	10
polar white glossy	9 3695 25 09	10
black glossy	9 3695 25 10	10
chrome glossy, galvanised	9 3695 25 18	10
chrome matt, galvanised	9 3695 25 28	10
chrome matt, lacquered	9 3695 25 68	10



Reverse polarity push-button, 6 contacts, with imprint for steps

Operating voltage	12 ... 24 V=	- e.g. for caravan step
Momentary-contact current at 12 V=	15 A	- double change-over contact, usable as NC or NO with separate input terminals
Momentary-contact current at 24 V=	7.5 A	- 6 contacts at the backside
Flat connector size (size width x size width)	4.8 x 0.8 mm	- with fast-on terminal connection

Suitable for	Order no.	Page
Contact protection box Ø 45 mm	9 1820 ..	63
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 191 ..	63
Contact protection box 3gang	9 1933	64

Design	Order no.	PU
anthracite matt	9 3697 25 05	10
black glossy	9 3697 25 10	10
chrome glossy, galvanised	9 3697 25 38	10



Reverse polarity push-button, 4 contacts, with imprint for beds

Operating voltage	12 ... 24 V=	- for e.g. height-adjustable beds
Momentary-contact current at 12 V=	15 A	- 4 contacts at the backside
Momentary-contact current at 24 V=	7.5 A	- with fast-on terminal connection
Flat connector size (size width x size width)	4.8 x 0.8 mm	

Suitable for	Order no.	Page
Contact protection box Ø 45 mm	9 1820 ..	63
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 191 ..	63
Contact protection box 3gang	9 1933	64

Design	Order no.	PU
anthracite matt	★ 9 3699 25 75	10
chrome matt galvanised	★ 9 3699 25 78	10



Reverse polarity push-button, 4 contacts, with imprint for awnings

Operating voltage	12 ... 24 V=	- e.g. for caravan awning
Momentary-contact current at 12 V=	15 A	- 4 contacts at the backside
Momentary-contact current at 24 V=	7.5 A	- with fast-on terminal connection
Flat connector size (size width x size width)	4.8 x 0.8 mm	

Suitable for	Order no.	Page
Contact protection box Ø 45 mm	9 1820 ..	63
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 191 ..	63
Contact protection box 3gang	9 1933	64

Design	Order no.	PU
anthracite matt	9 3696 25 05	10
chrome glossy, galvanised	9 3696 25 18	10
chrome matt, galvanised	9 3696 25 28	10
chrome matt, lacquered	9 3696 25 68	10



Reverse polarity push-button, 6 contacts, with imprinted arrows symbol

Operating voltage	24 V=	- double change-over contact, usable as NC or NO with separate input terminals
Momentary-contact current at 12 V=	15 A	- 6 contacts at the backside
Momentary-contact current at 24 V=	7.5 A	
Flat connector size (size width x size width)	4.8 x 0.8 mm	
Design	Order no.	PU
chrome glossy, galvanised	8 3697 25 78	50

Suitable for	Order no.	Page
Contact protection box Ø 45 mm	9 1820 ..	63
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 191 ..	63
Contact protection box 3gang	9 1933	64

Appliance switch



On/off switch, 2-pole USA/CANADA with printing "0" and "I"

Rated voltage	250 V~	- with fast-on terminal connection
Switching current	16 A	
Flat connector size (size width x size width)	6.3 x 0.8 mm	
Switch UL listed.		
Design	Order no.	PU
polar white matt	9 4509 25 02	10
anthracite matt	9 4509 25 05	10
black matt	9 4509 05	10

Suitable for	Order no.	Page
Contact protection box Ø 45 mm, flat	9 1820 0 ..	63
Contact protection box Ø 45 mm	9 1820 ..	63
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 191 ..	63
Contact protection box 3gang	9 1933	64



1 - 10 V control units



1 - 10 V rotary potentiometer with frame

- setting knob	- basic brightness programmable
- soft locking	- e.g. for fluorescent lamps and LV halogen lamps
	- for switching and controlling electronic ballasts and 1 - 10 V Tronic transformers, 105 W
Operating voltage	230 V~
Frequency	50/60 Hz
Switching current	6 A
Control current	50 mA
Installation depth	22 mm
Axis dimension Ø	4 mm

To ensure same illumination, use only electronic ballasts and fluorescent lamps from the same manufacturers.

Possible to change fuse without removing cover.

Do not mount with Berker Integro contact protection boxes, flush-mounted housings or fixing clamping ring.

Interface according to DIN EN 61347-2-3

Design	Order no.	PU
Berker Integro - Design Flow		
brown matt	9 2891 25 01	10
anthracite matt	9 2891 25 05	10
grey glossy	9 2891 25 06	10
polar white glossy	9 2891 25 09	10



Accessories

Contact protection boxes

- flame resistant according to VDE 0606-1



Contact protection box Ø 45 mm, flat

Cable Ø	max. 10 mm	- only for switches and push-buttons
Installation depth	22 mm	- with 1 cable entry
Strain relief not suitable for flat cables.		

Design	Order no.	PU
grey, without strain relief	9 1820 03	200
grey, with strain relief	9 1820 01	200



Contact protection box Ø 45 mm

Cable Ø	max. 10 mm	- for switches and socket outlets
Installation depth	35.5 mm	- with 4 cable entries
Strain relief not suitable for flat cables.		
- 3 knock out openings		

Design	Order no.	PU
grey, without strain relief	9 1820 02	200
grey, with strain relief	9 1820	200
grey, with strain relief for fire protection applications	9 1820 20	200



Contact protection box Ø 49 mm

Cable Ø	max. 10 mm	- with 2 cable entries
Installation depth	38 mm	
Strain relief not suitable for flat cables.		

Design	Order no.	PU
grey, without strain relief	9 1887 01	200
grey, with 1 internal double strain relief on side	9 1887	200



Contact protection box Ø 49 mm, deep

Cable Ø	max. 12 mm	- with 2 cable entries on backside
Installation depth	45.5 mm	- 1 knock out opening
Strain relief not suitable for flat cables.		

Design	Order no.	PU
grey, with 1 external double strain relief	9 1883	200
grey, with 1 external double strain relief for fire protection applications	9 1883 20	200



Contact protection box 2gang

length	109 mm	- with 2 cable entries
Width	49 mm	- for vertical and horizontal mounting
Cable Ø	max. 12 mm	- 1 knock out opening
Installation depth	37 mm	

Strain reliefs not suitable for flat cables.
Only suitable for 2gang frames!

Design	Order no.	PU
grey, with strain relief	8 1915 01	100
grey, with 2 strain reliefs	8 1915 02	100
grey, with strain relief	9 1915 01	10
grey, with 2 strain reliefs	9 1915 02	10



Contact protection box 2gang vertical, deep

▶ 213

length	109 mm	- with 4 cable entries on backside
Width	48 mm	- for vertical mounting
Cable Ø	max. 12 mm	- 3 knock out openings
Installation depth	45.5 mm	

Strain relief not suitable for flat cables.
Only suitable for 2gang frames!

Design	Order no.	PU
grey, without strain relief	9 1911 02	100
grey, with 1 external double strain relief	9 1911	100
grey, with 2 external double strain reliefs	9 1911 01	100



Contact protection box 2gang horizontal, deep

▶ 213

length	48 mm	- with 4 cable entries on backside
Width	109 mm	- for horizontal mounting
Cable Ø	max. 12 mm	- 2 knock out openings
Installation depth	45.5 mm	

Strain relief not suitable for flat cables.
Only suitable for 2gang frames!

Design	Order no.	PU
grey, with 1 external double strain relief	9 1912	100
grey, with 2 external double strain reliefs	9 1912 01	100



Contact protection box 3gang

▶ 213

length	168 mm	- with 6 cable entries, 1 per side, top, bottom and 2 on backside
Width	49 mm	- for vertical and horizontal mounting
Cable Ø	max. 10 mm	- 5 knock out openings
Installation depth	38 mm	

Strain relief not suitable for flat cables.
All devices can optionally be arranged vertically or horizontally.

Only suitable for 3gang frames (except order no. 9 1819 25 18, 9 1978 25 18 and 9 1978 25 28).

Restricted installation options apply if the cable clamp is mounted on the front face.

Design	Order no.	PU
grey, with 1 strain relief	9 1933	10



Contact protection box Ø 58 mm for terminal attachment

▶ 213

Cable Ø	max. 10 mm
Installation depth	35 mm

Strain relief not suitable for flat cables.

Design	Order no.	PU
grey, without strain relief	8 1837 01	200
grey, with 1 internal strain relief	8 1837	200

Supplementary products



Fixing clamping ring

▶ 213

Hole Ø	50 mm
For Berker Integro inserts, e. g. for installation in a mirror.	

Design	Order no.	PU
grey, material thickness 5 mm	8 1836	200
dark grey, material thickness 4 mm	8 1836 01	200
polar white matt, material thickness 6 mm	8 1836 02	200

Suitable for
Contact protection box Ø 58 mm for terminal attachment

Order no.
8 1837 ..

Page
64



Blank plate

– with supporting plate

Design	Order no.	PU
brown matt	8 4516 25 01	200
anthracite matt	8 4516 25 05	200
grey glossy	8 4516 25 07	200
polar white glossy	8 4516 25 09	200
chrome matt, lacquered	8 4516 25 68	200
brown matt	9 4516 25 01	10
anthracite matt	9 4516 25 05	10
grey glossy	9 4516 25 07	10
polar white glossy	9 4516 25 09	10
black glossy	9 4516 25 10	10
black matt	9 4516 05	10
granite black, silk matt, lacquered	9 4516 25 45	10
Stainless steel matt, lacquered	9 4516 25 24	10



Mounting template 3gang, cardboard

For precise hole drilling for 1gang appliances and for 2gang and 3gang combinations.

Design	Order no.	PU
grey, cardboard	918 44	10



For precise hole drilling for 1gang appliances and for 2gang combinations.

Design	Order no.	PU
	9 1845 02	1



For precise hole drilling for 1gang appliances and for 2gang and 3gang combinations.

Design	Order no.	PU
	9 1845 03	1



Built-in socket for floating output

Conductor cross-section (rigid) max. 6 mm² – for centre plate with cut-out dia. 18.8 mm
 – with a green yellow signal ring
 For separate earthing of medical-technical equipment and lab equipment.
 Connection pins according to DIN 42801



Design	Order no.	PU
Built-in socket for floating output	4604	1



Plug 12 V

Operating voltage
Rated current

12 ... 24 V
max. 8 A

– with solder connection

Suitable for
Socket outlet 12 V
Socket outlet 12 V

Order no.
8 4517 ..
9 4517 ..

Page
45
45



Design
black matt

Order no.
4637

PU
1



Wire and duct entry

Also suitable for surface-mounted frames and housings from the flush-mounted ranges.

– for wire or 15 x 15 mm cable duct

Suitable for
Surface-mounted housing high

Order no.
9 1151 ..

Page
91

Design
white
polar white
black

Order no.
1813
1813 09
1813 05

PU
10
10
10

Products for Truma devices



Frame 1gang for Truma devices

To be used only for Truma devices!

Design
anthracite matt
chrome glossy, galvanised

Order no.
8 1971 25 05
8 1971 25 17

PU
200
200

brown matt
anthracite matt
grey glossy
polar white glossy
black glossy
chrome matt, lacquered
chrome glossy, galvanised
stainless steel matt, lacquered

9 1971 25 01
9 1971 25 05
9 1971 25 07
9 1971 25 09
9 1971 25 10
9 1971 25 68
9 1971 25 17
9 1971 25 24

10
10
10
10
10
10
10
10



Frame 2gang for Truma devices

To be used only for Truma devices!

Design
brown matt
anthracite matt

Order no.
8 1972 25 01
8 1972 25 05

PU
100
100

brown matt
anthracite matt
chrome matt, lacquered

9 1972 25 01
9 1972 25 05
9 1972 25 68

2
2
2



Frame 3gang for Truma devices

To be used only for Truma devices!

Design
brown matt
anthracite matt

Order no.
8 1973 25 01
8 1973 25 05

PU
200
200

brown matt
anthracite matt
chrome matt, lacquered

9 1973 25 01
9 1973 25 05
9 1973 25 68

2
2
2



Blank plate for Truma frame

Design	Order no.	PU
brown matt	8 1974 25 01	200
anthracite matt	8 1974 25 05	200
grey matt	8 1974 25 06	200
black matt	8 1974 25 03	200
chrome matt, lacquered	8 1974 25 68	200
brown matt	9 1974 25 01	10
anthracite matt	9 1974 25 05	10
chrome matt, lacquered	9 1974 25 68	10